



SM02

- ROTATION SPEED FROM 0 UP TO 36 RPM
- ROTATION SPEED MANAGEMENT BY INVERTER
- CLOCKWISE OR COUNTER/CLOCKWISE ROTATION POSSIBILITY
- POSITIONING EITHER ON THE RIGHT OR THE LEFT SIDE OF THE MACHINE
- EMERGENCY ROD OPERATED ALSO ON THE DECOILER REAR SIDE



Technical Data

Model	SM02
Loading Capacity	2500 Kg
Diam. Of Roll Holding Disc	1300 mm (51.2 in)
Rotating speed with electronic variation from 0 up to	36 rpm
Servo ventilated three-phase motor	0.75 Kw 230/400v - 50Hz
Gearbox with incorporated clutch	
Output torque	314 Nm
Vector inverter	230V 50/60Hz mono-phase
Net/Gross weight	460/510 Kg
Overall size without coil holder (L x W x H)	2000 x 1400 x 1700 mm

Decoiler Series



SM05

- **OSCILLATING ARM WITH LEAF SPRING**
- **COMPACT DIMENSION**
- **SPRING FOR ARM TENSION ADJUSTMENT**
- **ROTATION SPEED MANAGEMENT BY INVERTER**
- **CLOCKWISE OR COUNTER/CLOCKWISE ROTATION POSSIBILITY**
- **POSITIONING EITHER ON THE RIGHT OR THE LEFT SIDE OF THE MACHINE**
- **EMERGENCY ROD OPERATED ALSO ON THE DECOILER REAR SIDE**



Technical Data

Model	SM05
Loading Capacity	1200 Kg
Diam. Of Roll Holding Disc	1000 mm (39.4 in)
Rotating speed with electronic variation from 0 up to	40 rpm
Servo ventilated three-phase motor	0.75 Kw 230/400v - 50Hz
Gearbox with incorporated clutch	
Output torque	174 Nm
Vector inverter	230V 50/60Hz mono-phase
Net/Gross weight	280/320 Kg
Overall size without coil holder (L x W x H)	1500 x 1200 x 900 mm

The machine is shown without safety barriers for display purposes

The Manufacturer reserves the right to alter any information and/or picture provided in this brochure without notice.



**ADVANCED TECHNOLOGY
FOR WIRE AND METAL STRIP
PROCESSING**

OMCG s.r.l.
Via Moronata, 46
23854 Olginate (LC) ITALY
Tel. +39 0341 604244
Fax +39 0341 604247
omcg@omcg.com
www.omcg.com

North America OMCG Inc.
857 Industrial Drive
Bensenville (IL) 60106 USA
Tel. +1 630 8601016
Fax +1 630 8602333
naomcg@omcg.com
www.omcg.com

